



WELDING

DUTY CYCLE 60%

**POTENZA 200
CEL GE K**

ADVANTAGES

- Electronic equipment for high performance MMA welding with coated electrode: basic, high performance cellulosic, INOX and rutile. Specially designed to weld with cellulosic electrodes.
- Prepared for special TIG Lift Arc welding with tungsten electrode in an inert atmosphere.
- Suitable for all medium-sized jobs in the fields of maintenance, construction and structural steelwork.
- Unrivalled performance in its price range: 200A at 60%, no-load voltage 76Vdc.
- Easy welding, even for inexperienced users, thanks to the intelligent STAYER WELDING control including Hot Start, Arc Force and Anti Stick advantages to optimise the initial arc striking, improve arc stability during welding and prevent the electrode from sticking due to incorrect handling.
- Mechanical robustness against shocks and falls. Strong sheet metal chassis, rubber corners.
- Electrical robustness. Fully prepared for safe use with all types of generators: stabilised, AVR and inverter.
- Solid construction according to European specifications 2011/65/EU, 2014/35/EU, 2014/30/EU and EN/IEC 60974.



Optional (K)

DATA SHEET

Power (A, X=60%)	200	A
Electrode (mm)	1.6 - 5	mm
Weight (kg)	6	kg
Voltage (V)	230	V
Generator (KVA)	7 - 9	KVA
Size (cm)	42x30x14	cm
DINSE connectors	ø 1/2" (35 - 50)	

EQUIPMENT

- Power cable 3m x 2,5mm²
- Ground clamp 2m x 25mm²
- Electrode clamp 2m x 25mm²
- PE-HD Carry case



2mx25mm²



2mx25mm²



PROFESSIONAL QUALITY
www.stayer.es